



POORAM & POORAM

Mfg. of Speciality Lubricants

ISO 9001 CERTIFIED

ISO 45001 CERTIFIED

14B, 18th Main, Chikkallasandra,
Bangalore - 560 061. INDIA

+91-80-2639 2928

poorambag@yahoo.co.in

GST : 29AAEFP7091E1Z0

PRODUCT

RELEASE – ON[®] ULTRA - HPHS GREASE

This is a soft, buttery textured, synthetic, oil-based grease with special additives suitable for electronic industry. Free from Silicone.

APPLICATION

Lifetime lubrication for metal to metal/ metal to plastic/ plastic to plastic sliding surfaces. It is used in CNC machines for high speed vertical/ sliding movement. For bearings operating at moderate Speed and moderate load.

BENEFITS

Reduction of wear and, prolonged lubrication protects against corrosion and provides quiet operation of the machine.

PHYSICAL PROPERTIES

BASE	:	PAO, lithium soap
TEMPERATURE RANGE	:	- 45 °C to + 150 °C
APPEARANCE	:	White
DROP POINT	:	+ 195 °C
NLGI CONSISTENCY	:	1
WORKED PENETRATION	:	310-340
WATER WASHOUT AT + 80 °C, %	:	3.2
OIL EVAPORATION AT 24 hrs, + 100 °C , %:		0.4
OIL BLEED AT 24 hrs, + 100 °C , %	:	4
SHELF LIFE		18 Months